## **NOTES:**

- MEDIAN CURB SHALL BE WASHOE COUNTY TYPE I (DRAWING No. W−137). REFER TO DRAWING No. W−131B FOR CONCRETE REQUIREMENTS.
- 2. ADDITIONAL TRAFFIC CONTROL MARKINGS FOR ISLAND MAY BE REQUIRED BY COUNTY ENGINEER.
- 3. ALL LANDSCAPING WITHIN ISLAND SHALL BE IN ACCORDANCE WITH AASHTO AND APPROVED BY COUNTY ENGINEER.
- 4. ALL LANDSCAPING SHALL BE MAINTAINED BY HOMEOWNERS OR HOMEOWNER'S ASSOCIATION.
- 5. NO DRIVEWAY SHALL BE ALLOWED WITHIN 100' OF ANY PORTION OF AN ISLAND.
- 6. AN ENCROACHMENT/EXCAVATION PERMIT FOR THE ISLAND SHALL BE OBTAINED FROM THE COUNTY ENGINEER'S OFFICE.
- 7. ALL ROADWAY STRIPING FOR ISLAND SHALL BE PERFORMED BY DEVELOPER OR BUILDER.
- 8. COLORED CONCRETE MAY BE USED IF APPROVED BY COUNTY ENGINEER. MINIMUM CEMENT CONTENT SHALL BE 6.75 SACKS.
- 9. ADDITIONAL WIDTH (FRONT FACE TO FRONT FACE) MAY BE REQUIRED BY COUNTY ENGINEER.
- 10. MINIMUM 4" DIAMETER SUBDRAINS SHALL BE INSTALLED 1 FT BEHIND CURB AS SHOWN. SUBDRAIN SHALL BE INSTALLED MINIMUM DEPTH OF 3 FT BELOW THE TOP OF CURB, AND TIE INTO AN EXISTING DITCH OR STORM DRAIN.
- 11. THE MINIMUM STRUCTURAL SECTION FOR THE PAVEMENT WITHIN 50 FT OF NOSE OF ISLAND SHALL BE 5" OF ASPHALT ON 6" OF BASE.

DATE	REVISIONS	and the same of th
		/3/YAX\E\
		(*( <b>&lt;&gt;Λ</b> Σ )*)
		\*\*\*/
		1861

STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION

LANDSCAPE ISLAND NOTES SECTION NUMBER: 100 DRAWING NUMBER: W-110B

DATE:

2/21/2022